



2GIG-CNTRL2-345 WIRELESS CONTROL PANEL

FEATURES

FULL VOICE RESPONSE

The panel gives clear notifications that indicate system status, zone descriptions, alarms, and emergencies.

DATE, TIME & WEATHER DISPLAY*

With a touch, scroll through the date, and real-time weather forecasts and receive crime and severe weather alerts.

QUICK ACCESS

The One touch access buttons allow the quickest help possible in an emergency. The panel's LED lit buttons indicate the system's status.

USER FRIENDLY LCD TOUCH SCREEN

The easy-to-use color touch screen puts a wide range of security and home automation controls at your fingertips.

MULTIPLE ARMING OPTIONS

Secure your home by arming your system "AWAY" or "STAY." The Quick Arm/Exit and Bypass features offer added convenience.

* when accompanied with a GSM Cell unit and an active account with alarm.com

HOME AUTOMATION

The built in Z-Wave radio enables various home automation functions including HVAC, appliances, and lighting control.

TWO-WAY RESPONSE OVER CELLULAR*

Two-Way voice lets central station operators listen in and talk to you when a signal is received, ensuring that the proper emergency response personnel will be dispatched if necessary.

CONVENIENCE

The fully self contained panel contains a snap-in GSM Radio, a 24-hr. backup battery, and allows 8 user codes to monitor up to 48 wireless zones and 2 hard wire zones.

OVER-THE-AIR UPDATES*

There's no need to worry the panel's software becoming outdated. With our Over-the Air function, the panel will automatically be updated with the latest software.

REMOTE CONTROL OPTIONS*

Always be in control by remotely managing your system from a computer or web-enabled mobile phone (Blackberry, iPhone, etc.).

SPECIFICATIONS

- 48 Wireless zones
- 2 Hard wire Zones
- 8 Wireless Keys
- 4 Wireless Pads
- Built in Z-Wave radio
- Full Voice Response
- Remote Over-the-Air downloading
- 8 User Codes
- Chime by zone with multiple chime settings
- Rechargeable Backup Battery

DIMENSIONS



TOUCH SCREEN DIMENSIONS: 3.75" X 2.25"

ELECTRICAL

VOLTAGE

120 VAC @ 60 Hz input
14 VDC @ 1700 mA output

RECHARGEABLE BACKUP BATTERY

2000 mA, 7.2V Ni-mh battery pack

ALARM SOUNDER

~85db at 10ft.

WHEN ORDERING

2GIG-CNTRL2-345 [control panel](#)

2GIG-GSM2-345 [internal GSM radio](#)

2GIG-ANT1-345 [internal antenna](#)

2gig technologies
801.221.9162
2gig.com